



Product Service

# CERTIFICATE

No. Z2 072458 0020 Rev. 00

**Holder of Certificate:**

**E. Beckmann e.K.**  
Zu den Gründen 16  
23623 Dakendorf  
GERMANY

**Certification Mark:**



**Product:**

**swing seats**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

**Test report no.:**

713153280-06

**Valid until:**

2024-11-04

**Date,** 2019-11-12

(Tobias Hofmann)



Product Service

# CERTIFICATE

No. Z2 072458 0020 Rev. 00

## Model(s):

**10000X, 10001X, 10030Y, 10031Y, 10010X,  
10020X, 103000, 10410X, 10420X, 200500,  
200602, 200607, 200609, 200610, 200615,  
201615, 201617, 201630, 201700, 201750,  
201780, 201800, 201850, 201955, 203220,  
203320, 203240, 200625**

## Parameters:

Commercial safety rubber swing seat typ 3 10000X:

Width/Length/Height: approx. 450/150/40 mm

Weight without chain approx. 1.2 kg

Commercial safety rubber swing seat typ 1B 10001X:

Width/Length/Height: approx. 480/170/40 mm

Weight without chain approx. 1.5 kg

Commercial Rubber tube swing seat MIA one seater 10030Y:

Width/Ø: approx. 500/130 mm

Weight incl. chain approx. 6.3 kg

Commercial Rubber tube swing seat MIA two seater 10031Y:

Width/Ø: approx. 1000/130 mm

Weight incl. chain approx. 10.6 kg

Commercial safety rubber swing seat type 2 10010X:

Width/Length/Height: approx. 435/220/43 mm

Weight without chain approx. 2.7 kg

Commercial safety rubber swing seat type 1 10020X:

Width/Length/Height: approx. 435/175/33 mm

Weight without chain approx. 2.0 kg

Swing seat Porky 103000:

Width/Length/Height: approx. 460/150/25 mm

Weight without chain approx. 0.72 kg

Commercial safety rubber swing seat type 1A 10410X:

Width/Length/Height: approx. 464/170/32 mm

Weight without chain approx. 2.0 kg

Commercial safety rubber swing seat type 2A 10420X:

Width/Length/Height: approx. 465/235/35 mm

Weight without chain approx. 3.0 kg

Safety swing seat type Jumbo 200500:

Width/Length/Height: approx. 530/150/35 mm

Swing seat with tire 200602:

Specially manufactured car tyre Ø approx. 600 mm

With textile inlay and mounted swing seat

T147

TUV SUD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD  
ZERTIFIKAT ♦ CERTIFICATE ♦ 認證證書 ♦ CERTIFIKAT ♦ CERTIFICADO ♦ CERTIFICAT



Product Service

# CERTIFICATE

No. Z2 072458 0020 Rev. 00

Car tire swing seats 200607:  
Specially manufactured complete car tire Ø approx. 630 mm  
Textile inlay, with internal pipe holder with  
4 x M8 threaded bolts for chain fastening using ring nuts.  
Tyre complete with mounted chains.

Car tire swing seats 200609:  
Specially manufactured complete car tire Ø approx. 630 mm  
Textile inlay, with inner pipe holder with 4 x M8 threaded  
bolts for chain fastening using ring nuts.

Half tire without bottom plate 200610:  
Ø approx. 630 mm, new car tyre cut lengthwise  
Reinforced from below with galvanized tube holder.

Half truck tyres with bottom plate 200615:  
Ø approx. 1040 mm new truck tyre cut lengthwise  
Reinforced from below with galvanised tube holder  
with 4 x M8 threaded bolts for chain fastening

Pendulum seat 201615:  
Ø approx. 255 mm, 200 cm galvanised 6 mm chain  
with 1.8 m protection hose

Pendulum seat 201617:  
Ø approx. 255 mm, 200 cm 6 mm stainless steel chain  
with 1.8 m protection hose

Pendulum seat 201630:  
Ø approx. 255 mm with 1.8 m rope suspension Ø 25 mm  
rope with steel core  
At the upper end with 20cm chain

Commercial safety rubber Cradle swing seat Fynn 201700:  
Width/Length/Height (flat seat): approx. 425/225/35 mm  
Height of the bracket about 190 mm  
Weight with chain: approx. 8.25 kg

Safety swing seat for handicapped children Conny 201750:  
Width/Length/Height (flat seat): approx. 455/315/395 mm  
Height of the bracket about 327,5 mm above the seat  
Three-sided bracket, front chains with carabiner

Rubber safety cradle seat RoTos 201780.JH:  
Width/Length/Height (flat seat): approx. 435/195/30 mm  
Height of the bracket about 200 mm above the seat  
Weight with chain: approx. 6.5 kg

Rubber safety cradleseat Waabe 201800.JH:  
Width/Length/Height (flat seat): approx. 450/314/35 mm  
Height of the bracket about 165 mm above the seat

747



Product Service

# CERTIFICATE

No. Z2 072458 0020 Rev. 00

Rubber cradle seat Rico 201850:  
Width/Length/Height (flat seat): approx. 450/314/35 mm  
Height of the bracket about 165 mm above the seat  
Weight with chain: approx. 8.2 kg  
Three-sided bracket, front chains with carabiner

Safety swing seat type KADI 201955:  
Width/Length/Height: approx. 450/310/35 mm  
Weight without chain: approx. 3.0 kg

Rubber group swing 203220:  
Ring made from EPDM rubber, Ø 950 mm,  
with steel tube inside  
Fillings: stainless steel chain net  
6 mm chains, 4 x 1,20 m chains, connected to 2 x 75 cm  
on top for two point attachment (stainless steel)

Rubber group swing 203320:  
Ring made from EPDM rubber, Ø 950 mm,  
with steel tube inside  
Fillings: rope net  
6 mm chains, 4 x 1,20 m chains, connected to 2 x 75 cm  
on top for two point attachment (galvanized)

Rubber group swing 203240:  
Ring made from EPDM rubber, Ø 950 mm,  
with steel tube inside  
Fillings: rubber plate  
6 mm chains, 4 x 1,20 m chains, connected to 2 x 75 cm  
on top for two point attachment (galvanized)

Half tire with bottom plate 200625:  
Ø approx. 630 mm, new car tyre cut lengthwise  
Reinforced from below with galvanized tube holder.

Explanation of the article number additions X and Y:  
X stands for the colour variant for flat seats  
and can be assigned the numbers 0 - 3.  
The 0 is black, the 1 red, the 2 blue and 3 green.  
Y stands for the colour variant for tube swing seat and  
can be assigned the numbers 0 - 3.  
The 0 is black, the 1 blue, the 2 green and the 3 red.

**Tested  
according to:**

DIN EN 1176-1:2017  
EN 1176-1:2017  
DIN EN 1176-2:2017  
EN 1176-2:2017

**Production  
Facility(ies):**

072458

TNF